



**PRODUCT: JK Wrangler Kat Walk**

REV: C | 03-24-2022 | R60255

**READ INSTRUCTIONS IN FULL BEFORE INSTALLATION.  
QUESTIONS? CALL 916-760-4575 M-F 7:00 AM – 5:00 PM PST**

The ARS experience includes the ease of installation of our products. We design for most contingencies, but installation may be different based on different Jeep condition, configuration and/or year.

We are continually trying to improve our products and instructions – please help us by providing feedback and pictures if you find any part of the instructions that do not match your Jeep or are not easily understandable.

If you have any difficulties at all, please give us a call. Thank you and enjoy your ARS Products!

**IMPORTANT NOTE: We use Stainless Steel Hardware where possible. Therefore, a tube of Silver Anti-seize is provided and should be used on all bolts—only a small amount is needed.**

**WARRANTY INFORMATION:** This article is sold without warranty expressed or implied. No warranty or representation is made as to this products ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the way it is INSTALLED, USED and/or MAINTAINED. THE USER ASSUMES ALL RISK. By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these ARS products from Armored Works, LLC, its affiliates and distributors and agents as is and with all faults. The entire risk as to the quality and performance of these ARS products is with the purchaser. Working on your vehicle can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or safety critical work to a skilled mechanic. We take no responsibility for the incorrect use and/or installation of ARS products.

## Section 1: Tools & Notes on Installation



**Tools Required:** This list is the recommended tools for ease of installation. Other versions of the same tool can be used. For example, Allen Wrenches instead of Allen Drive Sockets.

7/32" Allen Wrench



**HOW TO USE THIS GUIDE:** The installation guide contains ALL steps for installation. Please read and follow the instructions in order of each page top to bottom and left to right.

**Jeep Model:** Instructions may apply to multiple Jeep models but are labeled separately where appropriate (i.e. TJ vs. LJ).

**Options:** Because of the number of component options we offer, these instructions may contain steps that will not match your configuration. You can skip these steps.

**Images:** Pictures are provided, and parts are labeled throughout the instructions. Each text box contains guidance based on the pictures next to it. The text will refer to alphabetical labels (A, B, etc.) found in the images.

**Installation Notes:** Terms may be used in the body of the instructions that you may not be familiar with, if you have any questions feel free to contact us at the number below, or email [techhelp@metalcloak.com](mailto:techhelp@metalcloak.com)

**QUESTIONS:** Any questions or comments about the instructions? Call us at 916-760-4575 M-F 7:00 AM – 5:00 PM PST.


# Section 2: Product Components



SHEET 1 OF 2

DC-0001 REV A

ITEM	PART NUMBER/DESCRIPTION	QTY.
1	WM-7015 WELDMENT, KAT WALK, JK	1
HK-R60255		
E 2	FA-2126 LOOP CLAMP 1.125 X 0.50H 0.25 HOLE	1
3	FS-04021 SBHCS, 0.25-20 X 0.63L SS 18-8 PLAIN	1
4	FS-04300 FLANGE NUT, 0.25-20 X 0.94H STL G5 ZINC	1
5	FS-06004 WASHER, 0.41ID X 0.81OD X 0.05TH SS 18-8	4
6	FS-06010 SBHCSC, 0.38-16 X 1.0L SS 18-8 PLAIN	4



THE INFORMATION CONTAINED ON THIS DRAWING IS THE EXCLUSIVE PROPERTY OF ARMORED WORKS, LLC. UNAUTHORIZED REPRODUCTION IS PROHIBITED.



**DO NOT SCALE DRAWING**

PART NUMBER/DESCRIPTION: R60255 KAT-WALK, JK

## Section 3: Installation Instructions



### Step 1: Install the Kat Walk

- A. ARS recommends using a second person to help hold the kat walk to the front hoop.
- B. Align the kat walk holes to the hoop.
- C. Loosely install the washers and bolts on each side of the kat walk.
- D. Using a 7/32" allen wrench tighten all hardware.
- E. On the passenger side insert the antenna into the provided antenna clamp and secure to the mounting bracket using the provided hoop allen bolt and nut. Tighten with a 7/32" allen wrench.

