



PRODUCT: 4xE JL Wrangler SportGate Speaker Mount

REV: A | 03-16-2022 | II-6964

READ INSTRUCTIONS IN FULL BEFORE INSTALLATION.

QUESTIONS? CALL 916-631-8071 M-F 7:00 AM – 5:00 PM PST

The MetalCloak experience includes the ease of installation of our products. We design for most contingencies, but installation may be different based on different Jeep condition, configuration and/or year.

We are continually trying to improve our products and instructions – please help us by providing feedback and pictures if you find any part of the instructions that do not match your particular Jeep or are not easily understandable.

If you have any difficulties at all, please give us a call. Thank you and enjoy your MetalCloak Products!

IMPORTANT NOTE: We use Stainless Steel Hardware where possible. Therefore, a tube of Silver Anti-seize is provided and should be used on all bolts—only a small amount is needed.

WARRANTY INFORMATION: This article is sold without warranty expressed or implied. No warranty or representation is made as to this products ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED and/or MAINTAINED. THE USER ASSUMES ALL RISK. By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these MetalCloak products from Armored Works, LLC, its affiliates and distributors and agents as is and with all faults. The entire risk as to the quality and performance of these MetalCloak products is with the purchaser. Working on your vehicle can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or safety critical work to a skilled mechanic. We take no responsibility for the incorrect use and/or installation of MetalCloak products.

Section 1: Tools & Notes on Installation



Tools Required: This list is the recommended tools for ease of installation. Other versions of the same tool can be used. For example, Allen Wrenches instead of Allen Drive Sockets.



Socket & Ratchet Wrench

9/16" Socket



10MM Box Wrench
9/16" Box Wrench

T25 Torx Wrench or Socket



Snips

HOW TO USE THIS GUIDE: The installation guide contains ALL steps for installation. Please read and follow the instructions in order of each page top to bottom, and left to right.

Jeep Model: Instructions may apply to multiple Jeep models, but are labeled separately where appropriate (i.e. TJ vs. LJ).

Options: Because of the number of component options we offer, these instructions may contain steps that will not match your particular configuration. You can skip these steps.

Images: Pictures are provided and parts are labeled throughout the instructions. Each text box contains guidance based on the pictures next to it. The text will refer to alphabetical labels (A, B, etc.) found in the images.

Installation Notes: Terms may be used in the body of the instructions that you may not be familiar with, if you have any questions feel free to contact us at the number below, or email techhelp@metalcloak.com

QUESTIONS: Any questions or comments about the instructions? Call us at 916-631-8071 M-F 7:00 AM – 5:00 PM PST.

Section 2: Product Components



DC-0001 Rev B

SHEET 1 OF 1

	1	2	3	4	5	6	7	8
	ITEM	PART NUMBER/DESCRIPTION			QTY.			
	1	CP-6988 SPORTGATE SPEAKER MOUNT, 4XE, JL			1			
	2	FM-06050 NYLOCK FLANGE NUT, M6-1.0 X 9.1H STL C8 ZINC			2			
E	3	FS-06004 WASHER, 0.41ID X 0.81OD X 0.05TH SS 18-8			2			
	4	FS-06031 HHCS, 0.38-16 X 1.0L STL G5 ZINC			2			

Diagram illustrating the assembly components and their quantities:

- 1: CP-6988 SPORTGATE SPEAKER MOUNT, 4XE, JL
- 2: FM-06050 NYLOCK FLANGE NUT, M6-1.0 X 9.1H STL C8 ZINC
- 3: FS-06004 WASHER, 0.41ID X 0.81OD X 0.05TH SS 18-8
- 4: FS-06031 HHCS, 0.38-16 X 1.0L STL G5 ZINC

THE INFORMATION CONTAINED ON THIS DRAWING IS THE EXCLUSIVE PROPERTY OF ARMORED WORKS, LLC. UNAUTHORIZED REPRODUCTION IS PROHIBITED.

DO NOT SCALE DRAWING




PART NUMBER/DESCRIPTION 6964 SPORTGATE SPEAKER MOUNT, 4XE, JL

MetalCloak
A DIVISION OF ARMORED WORKS, LLC

Section 3: Installation Instructions

Step 1: Speaker Box Mount Installation

- A. Using a T25 wrench remove the speaker box from the stock tire carrier (A1) and disconnect the camera wiring (A2).
- B. Cut the plastic nub off the speaker box using a pair of snips.
- C. Using a 9/16 socket and wrench remove the side backspacing adjustment bracket hardware on the tire carrier.
- D. Slide the speaker box mount onto the backspacing adjustment bracket using the provided hardware.



Section 3: Installation Instructions



Step 2: Speaker Box Installation

- E. Loosely install the factory T25 bolts and provided nuts to the speaker and slide the speaker box onto the speaker mounting bracket ,
- F. Tighten the speaker box hardware using a T25 torx wrench and a 10mm wrench.
- G. Using a 9/16 socket and wrench tighten the adjustment bracket bolts.
- H. Reconnect the speaker box wiring.

